




Max 350 mm



600 / 1,700 litres



6.5 T

HIGH-PRESSURE CLEANING

CITYCOM 2.0

THE RETURN OF A LEGEND

The Rioned CityCom is the perfect combination of vacuum/pressure cleaner for hard to reach areas and car parks. This combination is at home in busy city centres and is ideal for quick interventions. The Riomote remote control allows all functions to be operated by one person.

PARKING GARAGE

The CityCom is available in two versions. The standard version has a total height of about 2.15 metres. There is also the option of shortening the cabin roof to allow access to car parks with a maximum entrance height of 2 metres. Its compact dimensions allow you to park it anywhere without causing unnecessary traffic disruptions.

POWERFUL PUMPS

Despite its compact construction, the CityCom is a full-fledged combination unit with a 1,700-litre dirty water tank and 600-litre clean water tank, deployable for cleaning severely soiled pipes or draining grease pits or flooded basements. The base of this combined unit is an MB Fuso Canter 6S15. A powerful high-pressure pump and a Juroop PNR 73 vacuum pump (7,200 lpm / 425m³ hour) ensure excellent performance.

STORAGE

The cabinets on both sides of the tank offer plenty of space for cameras and tools. On top of the combined unit is ample space for storing suction hoses. The swing-away panels make them easily accessible. The cabin accommodates two passengers.

A light and vision package on the CityCom ensures optimum safety. Two long LED lights on either side of the tank enable safe working even in the dark.



The CityCom offers plenty of storage options





- Total height of < 2 metres possible
- Powerful suction and vacuum pump
- 2,300 litres tank capacity
- Swivelling high-pressure reel



Swivel reel with eControl+ control cabinet

TECHNICAL SPECIFICATIONS

Chassis	MB Fuso Canter 6S15, 150 HP
Wheelbase	2,800 mm
Height	Standard height 2.15 m Optionally lowered to approx. 1.98 m
Dimensions (L x W x H)	5514 x 1900 x 2015/1980 mm
Tank capacity	600 litres of clean water (2 PE tanks), 1,700 litres of waste water (steel tank)
Drive	PTO
HP Pump Rioned/ Speck	200 bar - 60 lpm
Pump protection	Run-dry protection with overrun possibility
Vacuum pump	Jurop PNR 73, air-cooled, oil-lubricated (capacity 7,200 lpm, 425 m ³ /h, 0.8 bar suction, 0.49 bar compression)
Connections	3" inlet, 3" outlet
HP reel	80 metres ½" hose, hydraulically operated, 180° swivelling
Filling reel	35 metres NW 19 filling hose
Storage	Storage cabinets on both sides of the tank. Storage space above it for additional suction hose, accessible via folding top panel
Operation	Rioned eControl+ control box
Remote control	Riomote 9-channel remote control with start/stop, pump control, gas on/off, emergency stop.
Standard accessories	Nozzles, spray gun with lance, suction hoses

OPTIES

Safety and ergonomics	Light and Visibility package with warning lights, working lights at rear and on both sides, interior lighting
Riopulse pulsator	Pump adjustment to save water and for more unblocking power
Antifreeze tank	30-litre antifreeze tank with circulation capability to protect the pump in winter
Extra hose length	100 metres NW13 HD hose instead of 80 metres